

enLighten

Emergency/Corridor Luminaire



The Chamaeleon Deco 3 is a robust bulkhead light that is easy to customise, adjustable brightness and dual colour temperature switch.

Thanks to an integrated smart daylight sensor. your lights turn on only when needed. The Chamaeleon Deco 3 is a smart light that goes into standby mode at dusk and reaches full light when motion is detected. At dawn the luminaire switches off automatically to save enerav.

This versatile bulkhead comes with a dual colour switch, making it easy for you to achieve the colour temperature you need, choose from 3000K warm white or 4000K natural white. Having completely separate light circuits ensures colour consistency over the age of the fitting.

Ideal for every corridor, lobby and building exterior. It is available in emergency and nonemergency.

OPTIONS AND BENEFITS

- Impact Rating IP66
- Emergency & non-emergency options available
- Adjustable brightness 100%/70%/50% luminance options within same fitting
- Dual colour switch with the flick of a switch choose either 3000K warm white or 4000K natural white colour tone
- 2 & 3 Step sensor dimming offers full, standby & off modes
- Smart daylight sensor your lights only turn on when needed
- Flicker free
- Low standby power 0.5W to 5.5W
- Expected life >54,000 @L70 delivered by high quality LEDs
- 5 year warranty





*Only applicable for D3-CHAM/D3-CHAM-E

APPLICATIONS



CORRIDORS



FIRE STAIRS









FEATURES



SENSOR

















COMPLIANCE





WARRANTY

SELECTABLE BRIGHTNESS

enLighten

Chamaeleon Deco 3


PRODUCT RANGE

	Description	Lumens (lm)		Rated Power (W)	
Model #		Full light	Standby	Full light	Standby 10%
D3-CHAM	Chamaeleon Deco 3 Standard with built-in microwave motion & daylight sensor	1300 1000 700	25% 10% Off	16 11 8	2
D3-CHAM-E	Chamaeleon Deco 3 Emergency with built-in microwave motion & daylight sensor	1300 1000 700	25% 10% Off	17 12 9	3
D3-CHAM-P	Chamaeleon Deco 3 Standard	1300 1000 700	N/A	16 11 8	N/A
D3-CHAM-E-P	Chamaeleon Deco 3 Emergency	1300 1000 700	N/A	17 12 9	N/A
D3-CHAM-HO	Chamaeleon Deco 3 High Output With built-in microwave motion & daylight sensor	2250 1700 1200	25% 10% Off	23 16 11	3

TECHNICAL INFORMATION


Optical			
Light source	LEDs		
Lumen output	2250lm - 700lm		
CRI	Ra>80		
CCT	3000K or 4000K (colour selectable)		
Electrical			
Power consumption	16W Standard, 17W Emergency, 23W High Output		
Standby light level	25%, 10% & Off		
Standby power	0.5W - 5.5W		
Operating voltage	220 - 240 V AC, 50/60Hz		
Emergency light			
Battery type	6.4V 1500mAh LiFePO4		
Discharge time	90 minutes		
Environmental			
IP rating	IP66		
Impact rating	IK10		
Weight	2.5kg (standard), 2.9kg (emergency)		
Temperature range	-20°C to +40°C (standard) 0°C to +40°C (emergency)		
Material Composition (body)	Die Cast Aluminium		
Material Composition (diffuser)	Polycarbonate		
Expected Lifespan	>54,000 hours @ L70		
Controls			
Selectable brightness	Allows for adjustable brightness, select 1500 lm, 1000 lm or 700 lm		
Smart daylight sensor	Standby at dusk, full light when motion is detected and switches off automatically with morning light		
Integrated motion sensor	2 & 3-step dimming to standby level or off		
Spare Parts			
Replacement battery	6.4V 1500mAh LiFEPO4		
pack	Part # SPC-BATT-D3		
Warranty*	5 years (Battery 2 years)		
	Data subject to change without notice.		

PHOTOMETRICS



DIMENSIONS

Model shown: D3-CHAM



Lighting Council

MEMBER 2025

Model shown: D3-CHAM

COMPLIANCE

The Chamaeleon Deco 3 series meets or exceeds all relevant standards and regulatory requirements.

For a full compliance and testing list visit **www.enlighten.com.au**. IES files, warranty, installation and product guides are also available for download.

Sold nationally through major electrical wholesalers.

Data subject to change without notice.

* Refer to warranty policy