



enLighten

## Emergency/Corridor Luminaire



# Chamaeleon Deco 2

Versatile oyster light with selectable brightness & correlated colour temperature

The Chamaeleon Deco 2 is an elegant, slim and versatile decorative light, that is easy to customise, with adjustable brightness and dual colour temperature switch.

Thanks to an integrated smart daylight sensor, your lights only turn on only when needed. The Chamaeleon Deco 2 is a smart light that goes into standby mode at dusk and reaches full light when motion is detected. At dawn the luminaire switches off automatically to save energy.

This versatile bulkhead comes with a dual colour switch, making it easy for you to achieve the colour temperature you need, choose from 3000K warm white or 4000K natural white. Having completely separate light circuits ensures colour consistency over the age of the fitting.

Ideal for every corridor, lobby and building exterior. It is available in emergency and non-emergency.

### OPTIONS AND BENEFITS

- **Emergency & non-emergency** options available
- **Adjustable brightness** - 1500/1000/700 lumens options within same fitting
- **Dual colour switch** - with the flick of a switch choose either 3000K warm white or 4000K natural white colour tone
- **2 & 3 Step sensor dimming** - offers full, standby & off modes
- **Smart daylight sensor** - your lights only turn on when needed
- **Flicker free**
- **Low standby power** - 0.5W to 5.5W
- **Expected life >60,000 @L70** delivered by high quality Samsung LEDs
- **5 year warranty**

### APPLICATIONS



CORRIDORS



FIRE STAIRS



FOYERS



LOBBIES



TOILETS

### FEATURES



DAYLIGHT SENSOR



DUAL COLOUR TEMPERATURE



EMERGENCY



IK10 IMPACT RATING



IP44 INGRESS PROTECTION



MICROWAVE MOTION SENSOR



SAFETY COMPLIANCE



SELECTABLE BRIGHTNESS




5 YEAR WARRANTY

## PRODUCT RANGE


Model #	Description	Lumens (lm)		Rated Power (W)	
		Full light	Standby	Full light	Standby 10%
D2-CHAM	Chamaeleon Deco 2 Standard with built-in microwave motion & daylight sensor	1,500	25%	16	
		1,000	10%	11	2
		700	Off	8	
D2-CHAM-E	Chamaeleon Deco 2 Emergency with built-in microwave motion & daylight sensor	1,500	25%	17	
		1,000	10%	12	3
		700	Off	9	
D2-CHAM-P	Chamaeleon Deco 2 Standard	1,500		16	
		1,000	N/A	11	N/A
		700		8	

## DIMENSIONS



Model shown: D2-CHAM

## PHOTOMETRICS



Model shown: D2-CHAM

## COMPLIANCE

The Chamaeleon Deco 2 series meets or exceeds all relevant standards and regulatory requirements.

For a full compliance and testing list visit [www.enlighten.com.au](http://www.enlighten.com.au). IES files, warranty, installation and product guides are also available for download.

Sold nationally through major electrical wholesalers.



## TECHNICAL INFORMATION

Optical	
Light source	Samsung LEDs
Lumen output	1500 (max), 1000, 700 lumens
CRI	Ra>80
CCT	3000K or 4000K (colour selectable)

Electrical	
Power consumption	16W Standard, 17W Emergency
Standby light level	25%, 10% & Off
Standby power	0.5W - 5.5W
Operating frequency	50/60Hz
Operating voltage range	220 - 240 V AC

Emergency light	
Battery type	3.2V 3000mAh LiFePO4
Discharge time	90 minutes
Emergency classification	D40

Environmental	
IP rating	IP44
Impact rating	IK10
Weight	1.3kg (standard), 1.5kg (emergency)
Temperature range	0°C to +40°C
Material Composition (body)	Polycarbonate (UV stabilised)
Material Composition (diffuser)	Polycarbonate (UV stabilised)
Expected Lifespan	>60,000 hours @ L70

Controls	
Selectable brightness	Allows for adjustable brightness, select 1500 lm, 1000 lm or 700 lm
Selectable colour temperature	3000K or 4000K
Smart daylight sensor	Standby at dusk, full light when motion is detected and switches off automatically with morning light
Integrated motion sensor	2 & 3-step dimming to standby level or off

Warranty*	
	5 years (Battery 2 year)

Data subject to change without notice  
\* Refer to warranty policy